



DESCRIPTION

A medium pressure, standard pitch metallic hose. Standard sizes range between 6mm to 300mm but are also available up to 450mm. Suitable for up to 8,000 flexing cycles. 316L SS Liner.

APPLICATIONS

Applications with extreme conditions or variables such as temperature extremes, chemical compatibility, permeation concerns etc; High Temperature Hydraulic Oils, Steam, Chemicals and Petroleum products, Corrosive liquids & Gases, Compressed Air & Pneumatic liners, Cryogenic applications, Food & Beverage production, Nuclear plants and Steam lines, Fluids associated with high temperature and pressure in paper plants, Tyre moulds and Textile Machinery, Oil Refineries and Toxic applications.

CONSTRUCTION

Liner: 316 Stainless Steel Currugated Tube
Reinforcement & Cover: One layer of 316L stainless steel over braid

STANDARDS

ISO 10380:2012

TEMPERATURE

-200°C to +600°C

Size	ID (mm)	OD (mm)	Bend (mm) Static / Dynamic	WP/BP	Product Code
1/4"	6.2	10.8	25/85	120/480	T7011-006
5/16"	8.2	13.3	32/125	100/400	T7011-008
3/8"	10.3	15.5	38/140	90/360	T7011-010
1/2"	12.2	17.9	45/140	80/320	T7011-012
5/8"	16.2	23	58/160	70/280	T7011-016
3/4"	20.2	28.3	70/170	64/256	T7011-020
1"	25.4	33.7	85/190	50/200	T7011-025
1 1/4"	34.3	42.7	105/260	40/160	T7011-032
1 1/2"	40.1	51.1	130/300	35/140	T7011-040
2"	50.3	62.3	160/320	30/120	T7011-050
2 1/2"	65.6	83	180/410	24/96	T7011-065
3"	80.3	97	200/450	18/72	T7011-080
4"	100.8	119	290/560	16/64	T7011-100
5"	125.4	152.5	325/710	14/56	T7011-125
6"	150.8	177.5	380/915	10/40	T7011-150
8"	197	228	500/1015	8/32	T7011-200
10"	250.4	281.5	620/1270	7.5/30	T7011-250
12"	300.2	339.5	725/1525	6/24	T7011-300

FLEXMETALLIC INDUSTRIES

Units 1 & 2
West Lodge
Northampton, NN7 2QB
United Kingdom

Office: +44 (0)
Accounts: +44 (0) 1753 378 984
Email: sales@flexmetallic.com
Website: flexmetallic.com

Company Registration Number: GB 12862185
D-U-N-S: 226238688

DISCLAIMER

The information contained in this document is to the best of our knowledge, true and accurate, from sources believed to be reliable, we reserve the right to alter specifications without notice. Since conditions under which the products may be used are beyond our control, our recommendations are made without warranty or guarantee and should only be used as a guide. It is however the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of this product, and to determine the suitability of the product for the intended application or use. All technical data is subject to change according to technical updates.

FLEXMETALLIC INDUSTRIES

Units 1 & 2

West Lodge

Northampton, NN7 2QB

United Kingdom

Office: +44 (0)

Accounts: +44 (0) 1753 378 984

Email: sales@flexmetallic.comWebsite: flexmetallic.com

Company Registration Number: GB 12862185

D-U-N-S: 226238688